

# Cummins-ORNL\FEERC Combustion CRADA: Characterization & Reduction of Combustion Variations

W.P. Partridge (PI), G. Jatana, V. Prikhodko, J.E. Parks  
Oak Ridge National Laboratory


Sam Geckler (PI), Anthony Perfetto, David Koeberlein, Rick Booth, Lyle Kocher,  
Adam Wade, Raj Subramanian, Alex Woods, Ryan Green, Brian Reed,  
Karthic Kameshwaran, Suk-Min Moon, Sriram Popuri, John Helt,  
Feng Tao, Yifeng Wu, Kevin Augustin  
Cummins Inc.

Project ID:  
ACE077

Presenter: Bill Partridge  
[partridgewp@ornl.gov](mailto:partridgewp@ornl.gov)

2015 DOE Vehicle Technologies Program  
Annual Merit Review  
June 10, 2015, Arlington, Virginia

U.S. DOE Program Management Team:  
Gurpreet Singh, Ken Howden, Leo Breton



***This presentation does not contain any proprietary, confidential, or otherwise restricted information.***



# Overview

## Timeline

- Current SOW started FY13
- SOW extends through FY15
- New 3-year SOW submitted

## Budget

- 1:1 DOE:Cummins cost share
- DOE Funding:
  - FY2013: \$300k
  - FY2014: \$283k
  - FY2015: \$250k

## Barriers

- *From DOE VT MYPP:*
  - 2.3.1.A: advanced engine combustion knowledge
  - 2.3.1.C: Modeling for combustion control
  - 2.3.1.D: Effective engine controls
- *General*
  - *Engine combustion*
    - Intake-charge uniformity
    - Combustion uniformity & completeness
  - *Engine controls*
    - Variability & diagnostics
    - Lower-penalty control methods
    - Diagnostics for methods demonstrations
  - *Durability*
    - Combustion instabilities
    - Instability induced corrosion, erosion, etc.

## Partners

- ORNL & Cummins Inc.
- Cummins HD SuperTruck project

# Objectives & Relevance


## *Identify Origins of Multi-Cylinder Engine Fluctuations* to Accelerate Development of Advanced Efficiency Engine Systems

### Objectives

- Assess fluctuations in cylinder-charge components
  - External EGR & intake air
  - Internal EGR (residual & rebreathed residual-backflow)
  - Cylinder-to-cylinder & cycle-to-cycle perspective
- Apply insights to advance development
  - Validate & tune 1-D & 3-D design models
  - Assess specific hardware & architectures
  - Assess control strategies

### Relevance – Charge Uniformity impacts:

- Combustion uniformity
- Performance of advanced-combustion strategies (RCCI, PPCI)
- Required engineering margins (efficiency penalty, fuel economy)
- Durability & ultimate efficiency limits across all cylinders






# Milestones

## 2014 Milestone (on schedule for timely completion):

- ✓ **Q1:** Specify second laser for quantifying intake & residual-backflow CO<sub>2</sub>
  - i.e., external & internal EGR
- ✓ **Q2:** Assess methods for differentiating intake and residual-backflow CO<sub>2</sub>
  - Measure H<sub>2</sub>O, Temperature & CO<sub>2</sub>
- ✓ **Q3:** Bench-level demonstration of method for CO<sub>2</sub> differentiation
- ✓ **Q4:** Method assessment for measuring cylinder-residual variations

## 2015 Milestone (on schedule for timely completion):

- ✓ **Q1:** Analyze cylinder charge components using advanced EGR Probe
  - **Q4:** Compare analysis methods for determining cylinder charge from charge-component measurements






# Approach

## Develop & Apply Advanced Diagnostics

for Resolving Multi-Cylinder-Engine Cylinder & Cycle-Uniformity  
to Improve Models, Design, Control & Enable Advanced Efficiency

### CRADA



**Clean, Fuel-Efficient, Durable**

**Engines in the Marketplace**

**6.7L ISB (Dodge Ram)**




**ISV5.0 (Nissan Titan)**


**SuperTruck Demonstration**



# Technical Progress: Summary

- **Background: Proof-of-principle Backflow Measurements**
  - Resolve Backflow vs. EGR-Air via EGR Probe
  - Proposed: Multi-Color Probe & Charge Prediction Technique
- **Multi-Color EGR Probe**
  - Crank-angle-resolved  $\text{CO}_2$ ,  $\text{H}_2\text{O}$ , Temperature & Pressure
  - Joint development leveraging CRADA & SuperTruck efforts
- **CRADA Measurement Campaign**
  - Assess Advanced Intake Architectures
  - Spatiotemporal EGR Uniformity
  - Measurements to assess hardware, system & design models
- **SuperTruck Measurement Campaign**
  - Spatiotemporal Backflow Uniformity & Mapping
  - Assess Backflow, Stability and Control
- **Cylinder-Charge Stability**
  - Real-time Composition & Temperature predictions
  - Cylinder- and Cycle-specific uniformity assessment







- Measures CO<sub>2</sub>, H<sub>2</sub>O, T & P
- Leverages CRADA & SuperTruck
  - CRADA
    - Original EGR Probe development
  - SuperTruck
    - H<sub>2</sub>O diagnostic development at Purdue
  - CRADA & SuperTruck
    - 4-probe multi-plex system
    - Combined CO<sub>2</sub>-H<sub>2</sub>O probe instrument
- 4 parallel real-time probes
  - Simultaneous multi-cylinder data
- Improved analysis
  - Iterative baseline fit
  - Absorption profile fit to theory (vs. integration & calibration-factors)
  - Shifted-sawtooth laser ramp for real-time background subtraction
  - Improved wavelength calibration
  - 5kHz rate (200us, 1.2 CAD at 1k RPM)




# Tech.Prog.: ORNL & CMI Jointly Develop Multi-Color EGR Probe



- Extra-long EGR Probe
  - Reaches behind intake valve
  - Non-resonant with engine harmonics
- End-on-flow tip
  - CFD analysis & design at Cummins
  - 3-D 316-SS printed (at MAPI)
- Complex 4-optic collet & key
  - Designed at ORNL
  - Wire-EDM at Cummins
  - Rubber ferrule inserts cast (at MAPI)
- Anti-reflection coated probe optics
  - Reduces etalon noise
  - CO<sub>2</sub> purge windows AR coated too
- Enclosure
  - N<sub>2</sub> purging to eliminate background
  - Improved protection
- Can add other species
  - e.g., CO, O<sub>2</sub>, CH<sub>4</sub>
  - Multiplex on existing infrastructure



## Multi-Cylinder-Engine Campaign at Cummins Technical Center October 27-31, 2014



### Studying Intake-EGR Dynamics

- Building on previous campaigns
  - Experimental & Modeling work
- Studying various impacts
  - Mixer hardware (proprietary)
  - Cam profiles
  - Engine conditions
  - Transients & Unsteady operation


### Spatiotemporal EGR Mapping

- Origin of temporal dynamics varies
  - Pressure vs. flow induced
- Dynamics vary through the system
- Current focus is data application
  - Validating CFD design models
  - Understanding design tradeoffs
  - Optimizing system performance


# Tech.Prog.: SuperTruck Campaign Assesses Backflow & Uniformity

## Multi-Cylinder-Engine Campaign at CMI Development Facility September 22-26, 2014


### Spatiotemporal Backflow Mapping



### Measurements in Intake Runner






### CFD EGR Probe Comparison



- 2 Charge components directly measured
  - EGR-Air (baseline)
  - Combustion-residual backflow (pulse)
- EGR-Air uniform temporally & cyl-to-cyl
- Flat pulse indicates uniform backflow dilution
  - Dilution factor relates backflow to cylinder residual
  - Backflow  $\approx 20.8\%$  residual + 79.2% fresh EGR-air
- Width indicates backflow penetration depth
  - Use in Cylinder-Charge model
- Measured backflow wider than CFD
  - Flow in probed port much slower than modeled
- Many details & insights for assessing
  - Hardware, system, models, control

## Measurements & Modeling to predict Cylinder Charge

- Composition & Temperature
- Fluctuations (cycle- & cylinder-specific)



### Model Results:

Charge @ IVC	30% EGR w/ Backflow	30% EGR w/o Backflow
%CO <sub>2</sub>	2	1.8
T (K)	370	362

### EGR Probe Uncertainty Analysis:

Charge @ IVC	Uncertainty Analysis		Measured Charge Noise
	w/ Etalons	w/o Etalons	
%CO <sub>2</sub>	10%	1.5%	9%
T (K)	10%	1%	3%

- **Backflow variations reflect system stability**
  - Use backflow as a direct uniformity indicator
  - Backflow accounts for 10% of Charge CO<sub>2</sub>
- Currently limited by sensor uncertainty
  - 0.5% fluctuations impact engine performance
  - Varying etalons are a major noise source
  - Sensor noise dominates measurements
- Pathway to resolving 0.5% fluctuations:
  - Eliminate etalons
  - Increase absorption length
  - Modulation spectroscopy

# Responses to 2014 Review Comments

FY2014 AMR Review  
(5 Reviewers; max score: 4)

## Numerous Positive Comments:

- “unique approach via smart way of monitoring EGR variations”
- “creative approach,” “holy grail of tracking gas distribution”
- “demonstrated solid achievement for last few years”
- “innovative,” “good teamwork,” “future work well planned”
- Support DOE objectives “for both fuel economy and in-cylinder emissions”

Category	Score
Approach	3.40
Tech Progress	3.50
Collaboration	3.20
Future Research	3.30
<b>Weighted Average</b>	<b>3.41</b>

## Recommendations:

- Some questions re. how EGR Probe would be implemented in a practical & cost-effective way
  - *The EGR Probe is a research tool and not intended for on-vehicle implementation*
- Suggestion that other combustion parameters be studied in addition to EGR
  - *This has been proposed in our Future Work (e.g., AFR, mass flux, cylinder-head temperatures)*
- Several comments re. Cummins’ contribution & benefits, and contributions of the informal collaborators
  - *This has been highlighted in the presentation*
  - *A summary of contributions is provided in the Technical Backup Slides*
- Interesting to compare measured data to model predictions
  - *This is a CRADA priority; we have presented such here & in previous AMR presentations*
- Question re. if Cummins would apply the diagnostic to one of their multi-cylinder engines in the future
  - *cf. campaigns at CTC, which have occurred throughout CRADA ; two were highlighted here*
- Several comments re. adding non-CRADA participants to broaden project impact
  - *The CRADA strives to broadly benefit DOE and the Vehicle Technologies community*
  - *The formal (ACED Tech Team & AMR Reviewers) & informal (UCF) partnerships strengthen the project*
  - *CRADA is a formal CMI-ORNL agreement*
- Questions re. residual measurement, the EGR Probe’s invasive nature, and soot impact on quantification
  - *The CRADA team has performed experimental and numerical studies of these topics.*



# Collaborations & Coordination with Other Institutions

- **Cummins**

- CRADA Partner, Sam Geckler (Co-PI)

- **Cummins SuperTruck Program (ACE057, Friday 10-10:30am)**

- David Koeberlein (PI), Rick Booth, Lyle Kocher
- **Combustion-Residual Backflow Campaign**
  - Cooperative development of Multi-Color Multi-Species EGR Probe
  - Compared measurement to 3D-CFD model results
  - Used backflow data with Cylinder-Charge model

- **High-Dilution SGDI (ACE090, Wed 2:15-2:45pm)**


- Brian Kaul, ORNL (PI)
  - Applying EGR Probe to monitor cyclic-dispersion

- **University of Central Florida**

- Professor Subith S. Vasu & Students
  - Advancing MIR LED CRADA technology
  - Joint presentations and invention disclosures

- **Publications, Presentations and Patents**

- Patent: re. MIR LED EGR Probe
- Invention Disclosure: re. Fast CO-CO<sub>2</sub> probe
- Poster presentation
- ORNL-Cummins partnership recognized by Dr. Danielson, DOE EERE Assistant Secretary, for enabling clean & efficient engines for current & future vehicles



**United States Patent**  
Parks, II et al.

EGR DISTRIBUTION AND FLUCTUATION  
PROBE BASED ON CO<sub>2</sub> MEASUREMENTS

# Remaining Challenges & Barriers, and Proposed Future Work

## Remaining Challenges:

- Engine-system design models
- Developing advanced intake architectures for enabling improved efficiency
- Pathway to resolving 0.5% cylinder-charge fluctuations
- High-temperature exhaust measurements
  - Direct exhaust measurements
    - vs. via EGR loop
  - More direct cylinder-balance assessment
- CO-based combustion uniformity measure
  - Relevant to transient & high-EGR diesel, and stoichiometric combustion applications
- Measure other significant parameters influencing combustion uniformity

## Future Work (FY16-18):

- Compare models to measurements
  - Ongoing throughout CRADA
- Measurement campaigns at CTC
  - Assess hardware, system and control
  - Compare results to model-based expectations
  - Ongoing throughout CRADA
- EGR Probe modifications
  - Eliminate etalons
  - Increase absorption pathlength
  - Modulation spectroscopy
- Probe modifications
  - Reduce component contact, thermal-barrier coatings, and internal forced cooling
- Line-of-sight hardware
- Modify instrument to incorporate CO
  - Implement on existing HWG optics
  - Multiplex with existing CO<sub>2</sub> measurements
- Develop stretch technologies
  - Candidates include cylinder- & cycle-resolved:
    - AFR, mass flux, & cylinder-head temperature

# Summary

---

- **Relevance**

- CRADA work enables improved cylinder-to-cylinder & cycle-to-cycle uniformity
- This in turn enables DOE goals for improved fuel efficiency and durability

- **Approach**

- Develop diagnostics to measure multi-cylinder-engine spatial & temporal uniformity
- Apply diagnostics to advance engine technology
  - Assess specific hardware architectures
  - Tune, validate & improve design simulation tools (models)

- **Technical Accomplishments**

- Developed Multi-Color EGR Probe for crank-angle-resolved CO<sub>2</sub>, H<sub>2</sub>O, T & P measurements
- CRADA campaign measurement of advanced-intake architectures to assess CFD models
- SuperTruck campaign: assess 3D CFD models & measure charge-component fluctuations
- Developed measurement-based real-time model for predicting cylinder-charge parameters

- **Collaborations**

- Application of EGR Probe to Cummins' SuperTruck 55% BTE Goals
- EGR Probe application to DOE High-Dilution SGDI project & U. Central Florida partnership
- 1 patent, presentations & recognition by Dr. Danielson DOE Assistant Secretary for EERE
- EGR Probe available to users outside the CRADA

- **Future Work**

- Improve signal-to-noise & harden diagnostics for exhaust measurements
- Application campaigns at CTC on advanced development engine platforms
  - Assess hardware, design models and advanced closed-loop control strategies
- Develop new measurements for parameters relevant to combustion uniformity

---

## **Technical Back-Up Slides**



# Remaining Challenges & Barriers, and Proposed Future Work

## Remaining Challenges:

- EGR Probe hardware modifications
  - Incorporating optics for H<sub>2</sub>O spectroscopy
  - Avoiding resonance with engine harmonics
- Instrument modifications for Multi-Color Multi-Species EGR Probe measurements
- Modify instrument for closed-loop control studies
- Applications for advancing engine efficiency
  - EGR & charge uniformity, combustion uniformity
  - Tuning and validating design models
  - Two campaigns at Cummins Technical Center
- Determining net cylinder charge from component measurements

## Future Work (FY2015; i.e., from 2014 AMR):

- Modify probe to incorporate H<sub>2</sub>O & T optics
- Stiffen Long EGR Probe to avoid vibration
  - *In collaboration with SuperTruck team*
- Modify instrument to incorporate H<sub>2</sub>O & Temp.
  - Hardware: laser, multiplex unit, detection
  - Software: control, data acquisition & analysis
- CO<sub>2</sub> temperature-compensation methods
- Determine analysis speed & accuracy tradeoffs
  - Real-time analysis for control assessment
  - Slower post-analysis for improved accuracy
  - Requirements & tradeoffs to be defined by team
- Assess nature of cylinder-charge components
  - Spatial, cyl-to-cyl. & cyc.-to-cyc. uniformity
  - Calibrate simple scavenging model in GTPower
  - Campaigns in July (SuperTruck) & Oct. (CRADA)
- Apply campaign insights to initial development
- Further development
  - Models linking backflow to cylinder-residual nature
  - Weight factors for backflow & intake charge
  - Temporal (crank angle) integration methods

Completed

Completed

Completed

Completed

Initial Work & Model Completed

# Technical Progress: Summary of Participant Actions

- Summary of FY15 CRADA Participant Contributions
  - **Responding to AMR Reviewer request**
  - 1:1 DOE:Cummins cost share; i.e., Cummins matches DOE investment 1:1
  - Near and long-term research planning (Joint ORNL & CMI)
  - Diagnostics development, bench & mule-engine proof (ORNL lead)
    - Field-proofs at CTC (Joint ORNL & CMI)
  - Development engine & CTC resources (CMI lead)
  - Measurement campaigns (Joint ORNL & CMI)
  - Data analysis (ORNL lead for diagnostic, CMI for CTC sensors)
  - Interpretation (Joint ORNL & CMI)
  - Model comparison, assessment and modifications (CMI lead)
  - Next-steps and future-work planning (Joint ORNL & CMI)